




KVALITEST
INDUSTRIAL



Infeed Test System





► TYPE I-TS-3870 & TYPE MI-TS-3871



Infeed Test System – Type I-TS-3870

General Data:

- Power single system up to 650 kW
- Total power parallel system up to 1.3 MW
- Output voltage single system up to 1000 V
- Output current single system up to 1000 A (higher output current on request)




Typical applications:

- Battery simulation (BS)
- Battery test (BT)
- Testing fuel cell
- Testing solar panels
- Testing of charging stations (comemso)
- Power supply of trains

Applications (depending on configuration)

Infeed Test System – Type I-TS-3870:



Test of battery charging and discharging



Load for fuel cells (with safety function)



Power supply and power deduction of powertrain



source: Schaeffler


Testing power supply for fuses, contactors and MCCB



Test of DC-motors



Multi-Channel-Infeed-Test-System – Type MI-TS-3871



Types / Technical data

Typ	Rated power (kW)	DC Voltage (V)	DC-Current (A)	Typical current rise time 10 % - 90 % (ms)
I-TS-3870-300	60-120	5-300	200-1000	< 1
I-TS-3870-600	60-500	5-600	200-1000	< 1
I-TS-3870-800	100-500	5-800	200-1000	< 1
I-TS-3870-1000	100-650	5-1000	200-1000	< 1,3

AC - Input voltage / AC – Input frequency	380 / 400* / 440 / 480 / 500 / 690 V ±10 %, 3-phase, PE, 50 / 60 Hz ± 6 %
Measuring resolution	voltage: 16 Bit ADC current: 16 Bit ADC
Control accuracy	voltage 0.1 % fs current 0.1 % fs
Voltage tolerance dynamic (0 – 100 % INom in 3 ms)	< 3 % fs
Voltage ripple	≤ 0.1 % eff. fs
Current ripple	≤ 0.1 % eff. fs
Short circuit behavior	Short circuit proof (Ik < 3 kA)
Permissible ambient temperature	+5 to +40 °C
Climate class	1K21/1M11 according to EN60721 (85 % relative humidity non condensing with cabinet heating up to 95 % rel. humidity without condensing)
Distance from ceiling min.	300 (standard, IP20)
Installation	Operating area with restricted access installation on non-flammable floor
Protection class	IP20 according to IEC 60529 others on request
Safety	EN ISO 13849-1
Basic standard	EN 62040
EMC	EN 61000-2-4 grid disturbances EN 61000-6-2 interference immunity EN 61000-6-4 interference emission EN 61800-3 Kat C2 (A1) variable – speed electrical drives

Subject to change without notice (tech)

* Standard 400 V

Characteristics and basic equipment

- „Battery tester“ version
- Highly dynamic inverter
- Short circuit proof < 3 kA, < 8 kA at 1000 A systems
- Electrical isolation to grid
- Control accuracy 0.1 % fs
- Voltage ripple 0.1 % fs
- DC current measurement with 0.1 % fs accuracy
- Current rise time < 1 msec (300 - 800 V),
< 1.3 msec (1000 V)
- Seamless transition source/sink
- Main switch (switch disconnector with fuses in the AC input; lockable in Off-Position)
- Safety control for Performance Level d (PLd) in accordance with ISO 13849-1 / EN 60204-1
- TFT display with touch operation


- Stop button (black mushroom button) in cabinet door
- Voltmeter and ready indicator light in cabinet door
- DC output contactor
- Connection terminals for DC voltage measurement (0.1 % fs accuracy with sense lines)
- Connection terminals for external „Emergency Stop“
- Connection terminals for external „Stop“
- Connection terminals for calibrating case
- Interface MOD-bus / TCP-IP
- Interface CAN-bus („100 Hz“ with dbc file)
- Interface VNC over Ethernet
- Protection type IP20
- Air cooled
- High efficiency
- Noise-reduced version (rubber buffer, fan control)

Version „Battery simulator“

I-TS, 800 V DC, 600 A

Small voltage dip at load step

- Setting: constant voltage
- Max. accepted deviation of voltage at load step 0-100 % in 3 msec: 1 % fs = 8 V
- Measuring of transient voltage deviation and control settling time




typical course

Version „Battery tester“

I-TS, 1000 V DC, 1000 A, 100 kW


Fast current slew rate

- Output voltage 80 V DC
- Changing setpoint for current from - 1000 A to + 1000 A
- Measuring of current rise time (- 900 A to + 900 A) = 1.2 msec



typical course

Interfaces




Performance level „d“ (machine directive: EN ISO 13849-1)


- Redundant Hardware
- Redundant wiring
- Two separate channels
- Constant test of inputs and outputs
- Safe shutdown in case of error



Using batteries to increase max. power



Power supply with internal energy recovery for development and testing of e-powertrain



Power supplies for internal devices during service and repair of high speed trains

I-TS 250 kW 670 V/375 A




ICE



Control device


© AST, Wolnzach

Fuel cell testing




DC application: EVSE Test (DC EV Simulation)

DC application: EVSE Test (DC EV-Simulation).



DC application: EV Test (DC EVSE Simulation)

DC application: EV Test (DC EVSE-Simulation)



Options

1. Adaptation to test application

- Insulation monitoring device
- Operating mode battery simulator
- Operating mode battery simulator/tester switchable
- Output contactor with increased short-time withstand current
- Current range switching 100% and 10%
- Protective diode for sink mode
- Parallel control device
- PDSB (cabinet for additional options)
- Discharge Unit^[1]
- PDU (cabinet for DUT connection)
- Capacity box
- Safety performance level „e“

2. Adaptation to customer specification

- Adaptation safe shutdown time
- Intermediate discharge DC-link
- Emergency stop at door
- Door contact/door interlock
- Special door lock
- Special input voltage
- Adaptation to USA/CAN market
- Cabinet lamp/cabinet heating
- Single-wire marking
- Cabinet type Rittal - VX
- Base frame control cabinet
- Cabinet on wheels
- Special paint

3. Interfaces

- Remote contacts
- SCPI/EtherCAT/PROFIBUS/PROFINET
- Analogue
- High speed analogue I+
- High speed CAN (1 kHz)
- Remote control
- Matlab-Simulink
- Labview

4. Protection class control cabinet

- IP21/IP22/IP23/IP54
- Increase protection class from below
- Increase Protection class at open door IPX0B
- Fire protection

5. Cables and wires

- Halogen free cables
- Control cable/Sense cable/Power cable



Insulation monitoring device at DC output




DC-DC output contactor


^[1]A discharge unit always assumes a PDSB. From a rectifier output

Exemplary Applications

I-TS-3870 Single – Standard System




Changeover Test Cells / DUT



Testing one DUT and connecting simultaneously the second one

I-TS-3870 Parallel – System





***Innovation and quality from
Germany and Austria***



GUSTAV KLEIN GMBH & CO. KG

D-86956 Schongau · Im Forchet 3
D-86952 Schongau, Postfach 12 48
Phone +49(0)8861/209-0, Fax +49(0)8861/209-180
E-Mail: vertrieb@gustav-klein.com
www.gustav-klein.com

A-6401 Inzing/Tirol · Schießstand 2
Phone +43(0)5238/54209-0
Fax +43(0)5238/54209-23
E-Mail: vertrieb@gustav-klein.com
www.gustav-klein.com



EN / © 2021