

**High Temp. Compact** 

# Tension/Compression Load Cell LUXT-A



195°C
Compensated Temperature

# **Minimum Size**

 $(\phi 28 \times 34 \text{ mm})$ 

Comparison with our products

# **Application**










# Significant size and weight reduction compared to conventional models!



### **Main Specifications**

Rated Capacity	±500 N, ±1 kN, ±2 kN
Nonlinearity	Within ±0.5% RO
Hysteresis	Within ±0.5% RO
Rated Output	1.0 mV/V ±20%
Compensated Temperature	0 to 195°C (Non-freezing or Non-condensing)
Safe Overloads	150%
Weight	Approx. 80 g (Excluding cable)

Standard Accessories

Hexagon nut type3 materials SUS

Scan this for details



#### KYOWA ELECTRONIC INSTRUMENTS CO., LTD.

Global Sales Division:

3-5-1, Chofugaoka, Chofu, Tokyo 182-8520 Japan TEL: +81-42-489-7220 FAX: +81-42-488-1122 E-mail: kyowaoverseas.hp@d1.kyowa-ei.co.jp

Website: www.kyowa-ei.com

#### Safety Precautions

- Be sure to observe the safety precautions given in the instruction manual, in order to ensure correct and safe operation.
- Do not use in locations subject to significant water, dampness, steam, dust, or flammable gases. Doing so may lead to fire, electrical shock, or malfunction.
- Specifications and designs are subject to change without notice.
- $\blacksquare$  Please contact us if using the detailed products for special applications.
- Detailed company and product names are the trademarks or registered trademarks of their respective owners.
- The warranty details can be found on the "Product Warranty" attached to the product and on the following website. www.kyowa-ei.com/eng/company/quality/warranty.html
- Unauthorized use or reproduction of contents of this catalog are prohibited.

